

<b>REPORT OF CHANNEL CONDITIONS</b> <b>(FOR CHANNELS 400 FEET WIDE OR GREATER)</b>							<b>PAGE 1 OF 1 PAGE</b>	
<b>TO:</b> The Record							<b>FROM:</b> U.S. Army Corps of Engineers 26 Federal Plaza, ATTN: CENAN-OP-ST New York, NY 10278-0090	
<b>RIVER/HARBOR NAME AND STATE:</b> New York Harbor, NY - Red Hook Flats Anchorage						<b>MINIMUM DEPTHS IN EACH ¼ WIDTH OF CHANNEL ENTERING FROM SEAWARD</b>		
NAME OF CHANNEL	DATE OF SURVEY	AUTHORIZED PROJECT			LEFT OUTSIDE QUARTER (feet)	MID-CHANNEL		RIGHT OUTSIDE QUARTER (feet)
		WIDTH (feet)	LENGTH (nmiles)	DEPTH (feet)		LEFT INSIDE QUARTER (feet)	RIGHT INSIDE QUARTER (feet)	
<b>Reach A:</b> From a point approximately 1,620 feet seaward of RED #26 W/LIGHT & BELL EBB, to the approximate location of RED #28 W/LIGHT & BELL FLOOD.	File No. 5388/D/N3 Pg 2 & 3 of 6 19 & 20 December 2023	0 - 3,060	0.39	45	44.7	45.2	45.1	43.8
<b>Reach B:</b> From the approximate location of RED #28 W/LIGHT & BELL FLOOD, to the 330 feet landward of RED #30 W/LIGHT & BELL FLOOD	File No. 5388/D/N3 Pg 3 – 5 of 6 19 & 20 December 2023	3,060 - 4,620	0.51	40	42.9	39.1	38.7	39.0
<b>Reach C:</b> From 330 feet landward of RED #30 W/LIGHT & BELL FLOOD , to a location approximately 2,450 feet landward of YELLOW "A"/LIGHT EBB.	File No. 5388/D/N3 Pg 4 - 6 of 6 19 & 20 December 2023	4,620 – 3,310	1.51	35	41.6	36.6	33.1	33.3
<b>REMARKS:</b> <ul style="list-style-type: none"> <li>All reported depths are relative to Mean Lower Low Water (MLLW) datum.</li> <li>Channel reach lengths are in nautical miles.</li> </ul>								
<b>RED HOOK FLATS ANCHORAGE:</b> <ul style="list-style-type: none"> <li><b>Reach A:</b> Shoaling exists along the toe of the Right Outside Quarter. The controlling depth of -43.8 feet MLLW exists in the Right Outside Quarter approximately 2,420 feet landward of RED #26 W/LIGHT &amp; BELL EBB.</li> <li><b>Reach B:</b> Shoaling exists at the end of this reach in the Left Inside, Right Inside, and Right Outside Quarters of this reach. The controlling depth of -38.7 feet MLLW exists in the Right Inside Quarter in the approximately 1,520 seaward of RED #30 W/LIGHT &amp; BELL FLOOD.</li> <li><b>Reach C:</b> Shoaling exists in the Right Outside Quarter and into the Right Inside Quarter of this reach. The controlling depth of -33.1 feet MLLW exists near the center of the Right Inside Quarter, adjacent to YELLOW "C" W/LIGHT EBB.</li> </ul>								