

<b>REPORT OF CHANNEL CONDITIONS</b> <b>(FOR CHANNELS 400 FEET WIDE OR GREATER)</b>							<b>PAGE 1 OF 1 PAGE</b>	
<b>TO:</b> The Record							<b>FROM:</b> U.S. Army Corps of Engineers 26 Federal Plaza, ATTN: CENAN-OP-ST New York, NY 10278-0090	
<b>RIVER/HARBOR NAME AND STATE:</b> New York Harbor, NY - Red Hook Flats Anchorage						<b>MINIMUM DEPTHS IN EACH ¼ WIDTH OF CHANNEL ENTERING FROM SEAWARD</b>		
NAME OF CHANNEL	DATE OF SURVEY	AUTHORIZED PROJECT			LEFT OUTSIDE QUARTER (feet)	MID-CHANNEL		RIGHT OUTSIDE QUARTER (feet)
		WIDTH (feet)	LENGTH (nmiles)	DEPTH (feet)		LEFT INSIDE QUARTER (feet)	RIGHT INSIDE QUARTER (feet)	
<b>Reach A:</b> From a point approximately 1,700 feet seaward of RED #26 W/LIGHT & BELL EBB, to the approximate location of RED #28 W/LIGHT & BELL EBB.	File No. 5576/D Pgs 2 & 3 of 6; 30 April, 05 – 08 May 2025	0 - 3,060	0.39	45	44.9	45.0	45.0	43.9
<b>Reach B:</b> From the approximate location of RED #28 W/LIGHT & BELL EBB, to a point approximately 380 feet landward of RED #30 W/LIGHT & BELL EBB.	File No. 5576/D Pgs 3 & 4 of 6; 30 April, 05 – 08 May 2025	3,060 - 4,620	0.51	40	43.3	39.4	39.5	39.5
<b>Reach C:</b> From a point approximately 380 feet landward of RED #30 W/LIGHT & BELL EBB, to a point approximately 2,450 feet landward of YELLOW "A" W/LIGHT EBB.	File No. 5576/D Pgs 3 - 6 of 6; 30 April, 05 – 08 May 2025	4,620 – 3,310	1.51	35	41.3	36.3	34.0	31.3

**REMARKS:**

- All reported depths are relative to the Mean Lower Low Water (MLLW) datum.
- Channel reach lengths are in nautical miles.

**RED HOOK FLATS ANCHORAGE:**

- Reach A:** Shoaling exists sporadically throughout the Right Outside Quarter of this reach; some of which is located near or along the toe of the anchorage. The controlling depth of -43.9 feet MLLW exists in the Right Outside Quarter, along the toe of the anchorage, at a point approximately 215 feet seaward of GREEN #3 W/LIGHT & GONG EBB.
- Reach B:** Shoaling exists sporadically throughout the Left Inside, Right Inside, and Right Outside Quarters of this reach. The controlling depth of -39.4 feet MLLW exists in the Left Inside Quarter of this reach, at a point approximately 200 feet seaward of GREEN #5 W/LIGHT & BELL EBB.
- Reach C:** Shoaling exists sporadically throughout the Right Inside and Right Outside Quarters of this reach. The controlling depth of -31.3 feet MLLW exists along the toe of the anchorage, in the Right Outside Quarter, at a point approximately 2,525 feet seaward of the end of this reach.